

All dished up



Shooting table - the very word makes you think of something bulky, furniture-like, complex and labor intensive. You will see, that this is not necessarily true.

Shooting tables are among the most convenient tools in photography, when photographing artistic set-ups or small objects. Professionals have long known this. The classic shooting table or a similar construction of stands, background paper and a horizontal board is part of their standard equipment

Digital photography and its possibilities in particular make the benefits of a shooting table obvious. No matter if you want to document your teddy bear or model car collection, photograph expensive jewelry or precious coins for insurence purposes or need a quick picture for an internet auction - the shooting table provides support and background for the subject.









Some problems do not even come up because of features and properties of the cameras. A zoom lens with macro setting is standard equipment for most of the digitals, the desired frame can be controlled with help of the camera monitor and nobody has to worry about parallax differences.

The concave shaped background is the most important part of a shooting table. It provides a transition from foreground to background without a visible edge. There are additional possibilities if the concave-shaped background is made of translucent material and is illuminated from the bottom and/or from behind. Light and lighting are always important as some subjects need effective lighting to bring out their features.

For the vast spectrum of tabletop photography Kaiser offers a variety of solutions to "dish up": Fixed and portable units, for large or small, heavy or light subjects, variable system-based solutions with different components or complete units.

When your meal is dished up, everything should be nicely arranged. Why not do it the same way with your product shots and still lifes?










TopTable PRO – The Compact Studio

Tabletop photography on a professional level - that is what the TopTable PRO is designed for. In a floorspace of only 34 x 34 in. (85 x 85 cm) it offers a complete photographic studio with great versatility.





To isolate objects entirely from any background, the basic table can also be fitted with a crystal-clear acrylic-glass add-on table.

There are also side mounting brackets which can be used to attach lighting units from the Kaiser camera stand range. The lights can also be positioned underneath the acrylic-glass plate for transmitted light shots.

The shooting table can be easily wheeled on its castors to any point without having to dismantle lights and stands and set them up again.






This is the regular set-up: Basic Support 5921 and Acrylic-Glass Plate 5924 are all you need for standard tabletop photography. In addition you may use paper background of any width as shown in the picture at the bottom.

There is a suitable set of Soft Lights 5867 available, that can be attached directly to the shooting table.





If photographed objects should appear to float in mid-air against the background, the Add-On Table 5922 is required.








Some objects are too heavy, the acrylic-glass plate would bend under extreme load. That is why the Wooden Base Plate 5925 is available. The concave shaped background is formed by background paper of any desired width. The Background Carrier 5923 holds the background paper roll.

The Lighting Kit 5868 is mounted underneath the shooting table for transmitted light shots.





5921 Basic Support

Strong square tube frame fitted with heightadjustable feet at the front and lockable castors at the back. Mounting facilities for reflected and transmitted lighting.

Height: 1.78 m (70 in.)

Working height: 80 cm (31.5 in.) Required floor space: 85 x 85 cm (33.5 x 33.5 in.)

The "TopTable PRO" main table consists of Basic Support 5921 and Acrylic-Glass Plate 5924.

5926 Mounting Adapter

To attach Kaiser lighting units (p. 77 and from p. 87) for reflective lighting to the Basic Support 5921. 2 pieces.

5924 Acrylic-Glass Plate

A white transparent background acrylic-glass plate that is mounted on the Basic Support 5921 to form a concave shaped base.

Width: 80 cm (31.5 in.)
Overall length: 168 cm (66.1 in.)

Thickness: 3 mm



5922 Add-On Table

Can be mounted on the basic table (consisting of the Basic Support 5921 and the Acrylic-Glass Plate 5924). The Add-On Table is supplied with a concave curved crystal-clear acrylic plate.

Dimensions (WxHxD): 85 x 102 x 80 cm (33.5 x 40.2 x 31.5 in.)



5925 Wooden Base Plate

Can be mounted on the Basic Support 5921 (with or without Acrylic-Glass Plate 5924 attached). The matt grey laminated wooden plate is used in conjunction with paper background.

Dimensions: 85 x 56 cm (33.5 x 22 in.)



5923

Background Carrier

The carrier is mounted on the Basic Support 5921. Permits space-saving bearing of a background roll. Especially suited in combination with the Wooden Base Plate 5925.

Width: 85 cm (33.5 in.)



5867 Reflected Light Illuminating Set



Is mounted to the Basic Support 5921.Consists of two softlights and holding rods with mounting adapters. Lights can be slid, pivoted and adjusted in height. Vertical holding rods have height marks and can be tilted to different angles. Fitted with two daylight fluorescents each, high-gloss inner finish and high-frequency operating system. Separate control box.

4 x 36 W Lamps: Color temperature: 5400 Kelvin CRI: 90-100 (1A)

Reflector size: 50 x 21 cm (19.7 x 8.3 in.)



5868

Transmitted Light Illuminating Set



Is mounted to the Basic Support 5921. Consists of two tiltable softlights, fitted with two daylight fluorescent lights each, high-gloss inner finish and high-frequency operating system. Separate control box.

4 x 36 W Lamps: Color temperature: 5400 Kelvin CRI: 90-100 (1A) Reflector size:

50 x 21 cm (19.7 x 8.3 in.)



5582

Filter Holders

Guiding rails for slide-in filters for attachment to Reflected Lighting Unit 5867 and Transmitted Lighting Unit 5868. 2 pairs.

5583


Diffusion Screens

Fine structure acrylic glass. Can be mounted in conjunction with Filter Holders 5582 to Lighting Units 5867 and 5868. 2 pieces.

5594 **Polarizers**

Can be mounted in conjunction with Filter Holders 5582 to Lighting Units 5867 and

5868. 2 pieces.



The Studio on Your Desk



"TopTable" is a classic among the compact shooting tables. "TopTable" is not only a modular system with various components, but also a compact unit with "desk-top size" dimensions of 20 x 19".

Whether used as a complete digital desktop studio or composed of different components to specific requirements: "TopTable" copes with all problems of small object photography.

Product shots, catalog photos, internet pictures, creative stills, scientific photography, shots of medical preparations and instruments: possible fields of applications are only limited by the size of the subject.

Standard shooting situations with reflected light, silhouetting by background lighting, floating images, shots using a glass plate or a light tent – "TopTable" will always provide a solution.

For more possibilities on desktop photography look at the products from page 17 on.



5993-96 Table-Top-Studio "digital"

Complete desktop studio consisting of Small Product Table 5931 and a lighting unit. Product table with white transparent concave shaped acrylic background. Required desk space approx. $50 \times 50 \text{ cm } (20 \times 20 \text{ in.})$. Lighting unit consists of two small soft lights for even and smooth illumination. Holding rods with multiple orientation possibilities, screw-on clamps for attachment.

5994 and 5996 include an extra camera clamp comprising a 55 cm (21.7 in.) swanneck arm for cameras up to 600 g (21 oz.), ball head with 30 mm (1.2 in.) base and 1/4" camera thread plus a universal desk clamp for boards up to 30 mm (1.2 in.) thick or tubes up to 55 mm (2.2 in.) diameter.

5993 Table-Top-Studio "digital SN-HF"

With RB 218N HF high-frequency daylight lighting unit (5464). Interior reflectors for high light output. Mains leads with cord switch.

Lamps: 2 compact fluorescent lamps, 18 W each, 5400 Kelvin, CRI = 90-100.

5994 Table-Top-Studio "digital SN-HF plus"

Same as 5993, but with camera clamp.

5995 Table-Top-Studio "digital LED"

With RB 5020 DS LED daylight lighting unit (5465).

With 192 white high-CRI LEDs per light. Lights can be continuously dimmed separately or in combination. Dimmer includes switch-off position. Colour temperature 5600 Kelvin, CRI > 85, angle of radiation: 60°.

5996 Table-Top-Studio "digital LED plus"

Same as 5995, but with camera clamp.













5930 TopTable-Set

Three-piece set made up with components of the "TopTable" small product table system. Consisting of basic table with transparent acrylic plate (5931), add-on table with clear acrylic plate (5932) and holding frame for accessories (5934).

5935 Base Stand

For Small Product Table (5931). Permits the use of different types of lighting set-ups or larger light troughs underneath the small product table.

Dimensions (WxHxD): approx. 510 x 310 x 480 mm (20.1 x 12.2 x 18.9 in.)

5931 Small Product Table

Compact product table for table-top photography and reproduction. Table top/back-ground of transparent acrylic.

Dimensions (WxHxD): approx. 510 x 615 x 480 mm (20.1 x 24.2 x 18.9 in.)

5932 Add-On Table

Product table with clear acrylic plate to be set on the Product Table 5931 or to be used separately.

Dimensions (WxHxD): approx. 510 x 415 x 405 mm (20.1 x 16.3 x 15.9 in.)

5933 Glass Add-On Table

Flat product table for 5931 with glass top. Dimensions (WxHxD): approx. 510 x 160 x 405 mm (20.1 x 6.3 x 15.9 in.)

5934 Holding Frame

For holding foils, clamp-on lamp holders or similar accessories with the included holding clamps. Attaches to Product Table 5931 and 5932. Dimensions (WxD): approx. 510 x 480 mm (20.1 x 18.9 in.)



5465 RB 5020 DS TopTable Lighting Unit

LED daylight lighting unit comprising two small soft lights for even and smooth illumination, each equipped with 192 white high-CRI LEDs. Lights can be continuously dimmed separately or in combination. Dimmer includes switch-off position.

Lights are tiltable and adjustable in height. Angle of vertical arms adjustable by lock joint. Mounted with strong die-cast clamp bases. Clamping width up to 48 mm (1.9 in.).

Colour temperature: 5600 Kelvin

CRI > 85

Angle of radiation: 60°



5464 RB 218N HF TopTable Lighting Unit

Cold light lighting unit comprising two small soft lights, each equipped with a daylight fluorescent lamp. High frequency operating system. Main leads with cord switches.

Lights are tiltable and adjustable in height. Angle of vertical arms adjustable by lock joint. Mounted with strong die-cast clamp bases. Clamping width up to 48 mm (1.9 in.).

Lamps: 2 x 18 watt

Colour temperature: 5400 Kelvin

CRI = 90-100



Shooting Tables



2405/25 "prolite basic 2" Soft Light Source

Light Box as a daylight type backlight source for "TopTable" product table system.

Illuminated area: 50 x 30 cm (19.7 x 11.8 in.)

Lamps: 2 x 13 Watt, 5400 K

2136. 2476

Dimensions (WxHxD): 562 x 60 x 364 mm (22.1 x 2.4 x 14.3 in.)

"prolite basic 2 HF" Soft Light Source (2425) with additional high-frequency operating system.

5400K, 13W

5054



55 cm (21.7 in.) long gooseneck arm for cameras up to 600 g (21 oz.), ball head with 30 mm (1.2 in.) base and 1/4" camera thread. Universal table clamp with clamp range up to 30 mm (1.2 in.) on boards or 55 mm (2.2 in.) on tubes.



3439 **Diffusing Foil**

For producing soft, shadow-free illumination. Attaches to Holding Frame 5934 of "TopTable" product table. Can be cut to required size.

Dimensions: approx. 60 x 760 cm (23.6 x 300 in.)



5863-64 Desktop Shooting Kit

Comprehensive kit for object photography. Comprises a "Cube Studio" light tent for even and soft light distribution and two lights on desktop stands.

Cube studio with detachable front cover with slot for camera lens and two reversible textile backdrops white/grey and black/blue. Easy to set up, folds up automatically. Can be folded down to compact size. Includes carrying pouch. Reflector lights with ceramic socket for photofloods up to 250 watts (2 energy saving lamps, 25 W each, code no 3110, are included), swivel joint, umbrella mount and on/off switch. Detachable reflector, includes diffusing cover for soft light. Light stands with two-section telescopic center column, 16 mm standard spigot and 1/4" connection thread, setting height 35-70 cm (13.8-27.6 in.), max. load 3 kg (6.6 lbs.). Not available in 120 V.

5863: with Cube Studio 50 x 50 x 50 cm (20 x 20 x 20 in.) (5893)

5864: with Cube Studio 90 x 90 x 90 cm (35 x 35 x 35 in.) (5894)

5893-94 Cube Studio Light Tent


Cube-shaped light tent for even and soft illumination when shooting small objects. Detachable front cover with slot for camera lens. Easy to set up, folds up automatically. Can be folded down to compact size.

Includes two reversible textile backdrops white/grey and black/blue and zippered carrying pouch with wrist strap.

5893: 50 x 50 x 50 cm (20 x 20 x 20 in.)

5894: 90 x 90 x 90 cm (35 x 35 x 35 in.)





Shooting Tables



For small object photography. Suitable for product shots and internet images. White translucent surfaces provide for even and soft illumination. Umbrella-type construction makes set-up and fold-down easy. Comes with reversible textile background (white and grey) and protective cover with carrying straps.

5891: Floor size: 62 x 62 cm (24.5 x 24.5 in.), height: 51 cm (20 in.)

5892: Floor size: 75 x 75 cm (29.5 x 29.5 in.), height: 65 cm (25.5 in.)



5875-76 ConCave" Background


Flat and flexible plastic plate with holes on both sides and tightening cord. The plate can be bent in the desired shape and then be fixed by means of two "beads" and choice of respective holes.

Dimensions of flat plate: approx. 60 x 30 cm (23.6 x 11.8 in.)

5875: Opaque plate for shooting with reflected light.

5876: Transparent plate, for shooting with reflected and backlight.





This shooting table is pre-tailored from one single press board and is assembled by the user. The background made of flexible plastic material is inserted into the assembled table and fixed by velcro fittings. The evenly curved background ("open tube" outline) improves the distribution of light on the subject.

Side frames of the table provide attachment points for one or more lighting modules in vertical or horizontal position.

Dimensions (WxHxD, incl. background): 77 x 60 x 84.5 cm (30.3 x 23.6 x 33.3 in.)



5884 Lighting Module



5567

For 5883. One or more modules can be attached in horizontal or vertical position.

Aluminum housing with interior reflector, equipped with 36 watt daylight fluorescent lamp and high-frequency ballast. Mains lead with cord switch.

Reflector size: approx. 45 x 6.4 cm (17.7 x 2.5 in.)



5861-62 Desktop Lighting Kit

For still life and small product photography, e.g. in connection with shooting tables and light tents.

5861 Desktop Lighting Kit 1

Comprises reflector light for photofloods up to 250 W, with E27* ceramic socket, detachable reflector (ø 27 cm/10.6 in.), swivel joint, umbrella mount and on/off switch. Cord length approx. 3.8 m (12.5 ft.). Removable diffusing cover for soft light and desktop light stand 5859. Supplied with energy saving lamp 3110 (with 230 V version).



3110 3130 3124 4356 3128

5862 Desktop Lighting Kit 2

Comprises 2 Desktop Lighting Kits 1 (5861).



5860 Lamp Holder



3128

Suitable for photofloods up to 250 W max. With E27* ceramic socket, swivel joint, umbrella mount and on/off switch. Mounts on suitable tripods/stands with 16 mm standard spigot. Supplied without lamp.

Mains cord: approx. 3.8 m (12.5 ft.)



3110 Energy Saving Lamp

Daylight lamp with E27 socket. 25 watt, 6400 Kelvin, 1400 lumen, 230 volt. Start-up time < 2 sec. Service life up to 8000 hours.

Length: 158 mm (6.2 in.), diameter: 59 mm (2.3 in.)

See page 47 for more lamps.



5858-59 Desktop Light Stand

Two-section telescopic center column.

16 mm standard spigot and 1/4" connection thread. Max. load: 3 kg (6.6 lbs.)

5858: Setting height: approx. 22-38 cm (8.7-15 in.)

Length closed: approx. 24.5 cm (9.6 in.)

Weight: approx. 340 g (12 oz.)

5859: Setting height: approx. 35-70 cm (13.8-27.6 in.)

Length closed: approx. 39 cm

(15.4 in.)

Weight: approx. 530 g (18.7 oz.)





Since photography has become digital, more and more pictures of small objects are taken, included on websites to improve offering with internet auctions or to digitally archive collections. More and more images are also included with e-mails.

Studio-out-of-the-Box was designed to be a multiple problem solver: Camera mounting, object positioning and background are handled "out-of-the-box", and as an accessory there is also a lighting solution.

All will fit on your living room table - or wherever you want to place your temporary studio. Studio-out-of-the-Box is primarily a 30 x 45 cm / 12 x 18"

open-profile baseboard with a drawer and with a smart trapeze stand snuggling outside the baseboard. This makes it possible to fold it resulting in a rather compact unit that fits in the box.

The object is placed on the base-board, the drawer holds a frame that unfolds to carry the included back-ground roll. The background roll is only supported by the frame and that makes it easy to use wider back-grounds. If the drawer is removed completely and turned upside down, it increases the length of the studio base by 30 cm/12".

Opening the trapeze stand reveals its function: a camera mounted on the pivotable and relocatable platform can be positioned at any angle, any height and various distances from the object. The trapeze stand can be easily adjusted and holds the camera in any position. When shooting vertically from a top-down position the camera platform can be locked by two sliding guide bars in a way that the vertical position will remain as the trapeze is rotated.

An optional lighting unit can easily be attached to the main table and will also fit in the box.











5911 Studio-out-of-the-Box

Compact foldable studio for digital photography. Comprises table, background support, background material and trapeze stand for cameras up to 500 grams.

On the trapeze stand the camera can be positioned in many different positions and in different height and distance from the object. The camera platform is pivotable and relocatable and can be locked for vertical shooting position. Suitable for almost all digital compacts.

Table can be extended, background can be positioned in different heights. Background roll included, approx. 40 cm (15.7 in.) wide and 130 cm (51.2 in.) long. To support wider backgrounds a clip-on rail is included.

Dimensions (folded): 585 x 57 x 330 mm (23 x 2.2 x 13 in.)

Supplied with carrying box: $605 \times 485 \times 100$ mm ($23.8 \times 19.1 \times 3.9$ in.) (without handle)



Contains two lights, adjustable in height, pivotable and tiltable, mounted on tilting holding arms. High frequency operation with integrated electronic ballasts.

On/off switch on housing.

Lamps: 2 x 8 watts, approx. 4000 Kelvin, approx. 5000 hours service life.

Mains lead: 2 x 1.9 m (6.2 ft.)

5909/2133 Replacement Lamp

For 5914.

5909: Fluorescent lamp, 8 watts, approx. 4000 K, approx. 5000 hours service life. 1 piece.

2133: Fluorescent lamp, 8 watts, approx. 5400 K, approx. 8000 hours service life. 1 piece.)













Shooting Tables



6308-10 Clear Gear" Compressed Air

For touch-free dust removal from optical, fine mechanical and electronic equipment and components. With spray valve and capillary tube for inaccessible places.

6308: "Clear Gear" compressed air can, 200 ml, propane/butane mixture.

6309: "Clear Gear" compressed air can, 400 ml, non-inflammable fluorethane mixture, special high pressure version.

6310: "Clear Gear" compressed air can, 400 ml, propane/butane mixture, special high pressure version.



6381 Matt Spray

To remove undesirable reflections on shiny surfaces such as enamel, glass, plastic, high-gloss paint, chrome, etc. The photo matt spray is transparent, produces an even matt finish, dries quickly, adheres well and can be easily removed with water.

400 ml can.



6388 Adhesive Paste

Permanently elastic putty for holding, supporting and arranging photo objects. The putty can be formed at will and sticks to the object. It can be removed without leaving any residue.

Package with 250 g (8.8 oz.)



Polish paste for removal of scratches from acrylic glass, e.g. at shooting tables or light boxes. For more information see page 203.

6679 Acrylic Glass Cleaner

Special cleaning spray for acrylic glass. Supplied in pump spray bottle. For more information see page 203.

